

## Cámara IP D-Link DCS-2330L HD IR Micro SD / SDHC Wifi



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Cámara IP D-Link DCS-2330L HD IR Micro SD / SDHC Wifi al mejor...

Calificación: Sin calificación

**Precio**

Precio con descuento 208,74 €

Precio de venta 252,58 €

Precio de venta sin impuestos 208,74 €

24 h  
\*\*\*\*\*

[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Cámara IP D-Link DCS-2330L HD IR Micro SD / SDHC Wifi** al mejor precio.

**Marca**  
**Modelo**  
**Interfaces**

D-Link  
**DCS-2330L**  
- 802.11n wireless  
- 10/100 Fast Ethernet port  
- MicroSD/SDHC card slot para almacenamiento interno  
- 16GB MicroSD card incluida, soporta grabación hasta 7 días  
- HD resolution (1280 x 720)  
- H.264 and Motion JPEG compression  
- ePTZ viewing  
- Simultaneous multi-stream support  
- Privacy Mask feature  
- Supports multiple access lists

**Imagen**

## Características

### Cámara

- Sensor 1/4" Megapixel progressive CMOS
- Distancia IR: 5 m.
- Iluminación Mínima: 0 lux con IR LED
- Built-in Infrared-Cut Removable (ICR) Filter module
- Built-in PIR sensor (5 metre)
- Micrófono
- 10x digital zoom
- Focal length: 3.45 mm
- Aperture: F2.0
- Exposure time: 1/7.5 to 1/10,000 sec.
- Minimum object distance: 500 mm
- Angulo de visión:
  - (H) 57.8°
  - (V) 37.8°
  - (D) 66°

### Carcasa

- IP65 compliant weatherproof housing

### Funcionalidades imagen

- Configurable image size, quality, frame rate, and bitrate
- Time stamp and text overlays
- Configurable motion detection windows
- Configurable privacy mask zones
- Configurable shutter speed, brightness, saturation, contrast, and sharpness

### Video-Compresión

- Simultaneous H.264/MJPEG format compression
- H.264 multicast streaming
- JPEG for still images

### Video-Resolución

- 16:9 - 1280x720, 800x448, 640x360, 480x272, 320x176 up to 30 fps recording1
- 4:3 - 960x720, 800x592, 640x480, 480x352, 320x240 up to 30 fps recording1

### Audio

- AAC
- G.71

### Protocolos red

- IPv6
- IPv4
- TCP/IP
- UDP
- ICMP
- DHCP client
- NTP client (D-Link)
- DNS client
- DDNS client (D-Link)
- SMTP client
- FTP client
- HTTP / HTTPS
- Samba client
- PPPoE
- UPnP port forwarding
- RTP / RTSP / RTCP
- IP filtering
- QoS
- CoS
- Multicast
- IGMP
- ONVIF compliant

### Seguridad

- Administrator and user group protection
- Password authentication
- HTTP and RTSP authentication

### Requisitos acceso web

- Browser: Internet Explorer, Firefox, Chrome

### Gestión de eventos

- Motion detection
- Event notification and uploading of snapshots/video clips via e-mail or FTP
- Supports multiple SMTP and FTP servers
- Multiple event notifications
- Multiple recording methods for easy backup

**Gestión remota**

- Take snapshots/video clips and save to local hard drive
  - Configuration interface accessible via web browser
- Mobile Support
- Windows 8/7/Vista/XP, Pocket PC, tablet, or mobile phone-
  - mydlink™ mobile app for iOS and Android mobile devices

**D-Viewcam™ System Requirements**

- Operating System: Microsoft Windows 8/7/Vista/XP
- Web Browser: Internet Explorer 7 or higher Protocol: Standard TCP/IP

**D-Viewcam™ Software Functions**

- Viewing of up to 32 cameras on one screen
- Scheduled motion triggered, or manual recording options
- Supports all management functions in web interface
- Remote management/control of up to 32 cameras

**Otras características**

**Dimensiones**

- 105 x 66 x 45.7 mm

**Peso**

- 134 g ± 5%

**Alimentación**

- Output: 5 V DC, 1.2 A
- Input: 100 to 240 V AC, 50/60 Hz

**Consumo**

- 5 watts max.- -

**Temperatura**

- Operating: -25 to 45 °C (-13 to 113 °F)
- Storage: -20 to 70 °C (-4 to 158 °F)

**Humedad**

- Operating: 20% to 80% non-condensing
- Storage: 5% to 95% non-condensing

**Certificaciones**

- CE
- FCC class B
- C-Tick
- IC

11-11-2014 por FE4

**Fecha de revisión**

- Marca: D-Link
- Modelo: DCS-2330L
- Interfaces :
  - 802.11n wireless
  - 10/100 Fast Ethernet port
  - MicroSD/SDHC card slot para almacenamiento interno
  - 16GB MicroSD card incluida, soporta grabación hasta 7 días
- Imagen:
  - HD resolution (1280 x 720)
  - H.264 and Motion JPEG compression
  - ePTZ viewing
  - Simultaneous multi-stream support
  - Privacy Mask feature
  - Supports multiple access lists
- Características:
  - Cámara
  - Sensor 1/4" Megapixel progressive CMOS
  - Distancia IR: 5 m.
  - Iluminación Mínima: 0 lux con IR LED
  - Built-in Infrared-Cut Removable (ICR) Filter module
  - Built-in PIR sensor (5 metre)
  - Micrófono
  - 10x digital zoom
  - Focal length: 3.45 mm

- Aperture: F2.0
- Exposure time: 1/7.5 to 1/10,000 sec.
- Minimum object distance: 500 mm
- Angulo de visión: (H) 57.8° (V) 37.8° (D) 66°
- IP65 compliant weatherproof housing
- Configurable image size, quality, frame rate, and bitrate
- Time stamp and text overlays
- Configurable motion detection windows
- Configurable privacy mask zones
- Configurable shutter speed, brightness, saturation, contrast, and sharpness
- Simultaneous H.264/MJPEG format compression
- H.264 multicast streaming
- JPEG for still images
- 16:9
- 1280x720, 800x448, 640x360, 480x272, 320x176 up to 30 fps recording
- 4:3
- 960x720, 800x592, 640x480, 480x352, 320x240 up to 30 fps recording
- AAC
- G.711
- IPv6
- IPv4
- TCP/IP
- UDP
- ICMP
- DHCP client
- NTP client (D-Link)
- DNS client
- DDNS client (D-Link)
- SMTP client
- FTP client
- HTTP / HTTPS
- Samba client
- PPPoE
- UPnP port forwarding
- RTP / RTSP / RTCP
- IP filtering
- QoS
- CoS
- Multicast
- IGMP
- ONVIF compliant
- Administrator and user group protection
- Password authentication
- HTTP and RTSP authentication
- Browser: Internet Explorer, Firefox, Chrome
- Motion detection
- Event notification and uploading of snapshots/video clips via e-mail or FTP
- Supports multiple SMTP and FTP servers
- Multiple event notifications
- Multiple recording methods for easy backup
- Take snapshots/video clips and save to local hard drive
- Configuration interface accessible via web browser
- Windows 8/7/Vista/XP, Pocket PC, tablet, or mobile phone-
- mydlink™ mobile app for iOS and Android mobile devices
- Operating System: Microsoft Windows 8/7/Vista/XP
- Web Browser: Internet Explorer 7 or higher Protocol: Standard TCP/IP
- Viewing of up to 32 cameras on one screen
- Scheduled motion triggered, or manual recording options
- Supports all management functions in web interface
- Remote management/control of up to 32 cameras
- Otras características:
  - Dimensiones
  - 105 x 66 x 45.7 mm
  - 134 g ± 5%
  - Alimentación
  - Output: 5 V DC, 1.2 A
  - Input: 100 to 240 V AC, 50/60 Hz
  - Consumo
  - 5 watts max.
  - - Temperatura
  - Operating: -25 to 45 °C (-13 to 113 °F)

- Storage: -20 to 70 °C (-4 to 158 °F) Humedad
- Operating: 20% to 80% non-condensing
- Storage: 5% to 95% non-condensing Certificaciones
- CE
- FCC class B
- C-Tick
- IC
- Fecha de revisión: 11-11-2014 por FE4

#### **Comentarios**

Aún no hay comentarios para este producto.