

## Placa Base con CPU Integrada ASRock 90-MXGUK0-A0UA



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Placa Base con CPU Integrada ASRock 90-MXGUK0-A0UA al mejor...

Calificación: Sin calificación

### Precio

Precio con descuento 57,14 €

Precio de venta 69,14 €

Precio de venta sin impuestos 57,14 €

24 h



[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Placa Base con CPU Integrada ASRock 90-MXGUK0-A0UA** al mejor precio.

Marca	Asrock
Modelo	D1800M
Plataforma	(90-MXGUK0-A0UA V2) - Formato m-ATX
Chipset	- Intel® H81 Express
CPU Soportados	- Intel® Dual-Core Processor J1800 (2.41 GHz)  (Integrado)
Memoria	- Dual Channel DDR3/DDR3L Memory Technology - 2 x DDR3/DDR3L DIMM Slots - Supports DDR3/DDR3L 1333/1066 non-ECC, un-buffered memory - Max. capacity of system memory: 16GB
Slots Expansión	- 1 x PCI Express 2.0 x16 Slot (PCIe2 @ x1 mode) - 2 x PCI Express 2.0 x1 Slots

Gráficos	<ul style="list-style-type: none"><li>- Intel® 7th generation (Gen 7) graphics</li><li>- DirectX 11.0, Pixel Shader 5.0</li><li>- Three graphics output options: D-Sub, DVI-D and HDMI</li><li>- Supports HDMI Technology with max. resolution up to 1920x1200 @ 60Hz</li><li>- Supports DVI-D max. 1920x1200 @ 60Hz</li><li>- Supports D-Sub max. 1920x1200 @ 60Hz</li><li>- Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI Port (Compliant HDMI monitor is required)</li><li>- Supports HDCP with DVI-D and HDMI Ports</li><li>- Supports Full HD 1080p Blu-ray (BD) playback with DVI-D and HDMI Ports</li></ul>
Puertos E/S, Conectores	<p>E/S panel traseiro:</p> <ul style="list-style-type: none"><li>- 1 x PS/2 Keyboard</li><li>- 1 x D-Sub</li><li>- 1 x DVI-D</li><li>- 1 x HDMI</li><li>- 3 x USB 2.0 (Supports ESD Protection (ASRock Full Spike Protection))</li><li>- 1 x USB 3.0 (Supports ESD Protection (ASRock Full Spike Protection))</li><li>- 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED)</li><li>- HD Audio Jacks: Line In / Front Speaker / Microphone</li></ul> <p>E/S Internos:</p> <ul style="list-style-type: none"><li>- 1 x Print Port</li><li>- 1 x COM Port</li><li>- 1 x TPM</li><li>- 1 x Chassis Intrusion</li><li>- 1 x CPU Fan (3 pin)</li><li>- 1 x Chassis Fan (3-pin)</li><li>- 1 x 24 pin ATX Power</li><li>- 1 x Front Panel Audio</li><li>- 2 x USB 2.0 (Support 3 USB 2.0 ports) (Supports ESD Protection (ASRock Full Spike Protection))</li></ul>
Otras Características	<p>Audio</p> <ul style="list-style-type: none"><li>- 5.1 CH HD Audio (Realtek ALC662 Audio Codec)</li><li>- Supports Surge Protection (ASRock Full Spike Protection)</li></ul> <p>LAN</p> <ul style="list-style-type: none"><li>- PCI-E x1 Gigabit LAN 10/100/1000 Mbps</li><li>- Realtek RTL8111GR</li><li>- Supports Wake-On-LAN</li><li>- Supports Wake-On-LAN</li><li>- Supports Lightning/ESD Protection (ASRock Full Spike Protection)</li><li>- Supports LAN Cable Detection</li><li>- Supports Energy Efficient Ethernet 802.3az</li><li>- Supports PXE</li></ul> <p>SATA</p> <ul style="list-style-type: none"><li>- 2 x SATA3 3.0 Gb/s Connectors, support NCO, AHCI and Hot Plug</li></ul> <p>Certificaciones</p> <ul style="list-style-type: none"><li>- FCC, CE, WHQL</li><li>- E/P/EuP ready (E/P/EuP ready power supply is required)</li></ul>
Fecha Revisión	18-05-2014 por FE4

- Marca: ASRock
- Procesador: Integrado
- Encapsulado: LGA1150
- Memoria: DDR3
- Formato: Micro-ATX
- Almacenamiento: SATA 3
- T. Gráfica: Requiere CPU con gráficos
- Otros:
  - USB 3.0
  - HDMI
  - DVI
  - VGA Sub-D

- Marca: Asrock
- Modelo: D1800M (90-MXGUK0-A0UAYZ)
- Plataforma:
  - Formato m-ATX
- Chipset:
  - Intel® H81 Express
- CPU Soportados:
  - Intel® Dual-Core Processor J1800 (2.41 GHz) (integrado)
- Memoria :
  - Dual Channel DDR3/DDR3L Memory Technology
  - 2 x DDR3/DDR3L DIMM Slots
  - Supports DDR3/DDR3L 1333/1066 non-ECC, un-buffered memory
  - Max. capacity of system memory: 16GB\*
- Slots Expansión :
  - 1 x PCI Express 2.0 x16 Slot (PCI-E2 @ x1 mode)
  - 2 x PCI Express 2.0 x1 Slots
- Gráficos:
  - Intel® 7th generation (Gen 7) graphics
  - DirectX 11.0, Pixel Shader 5.0
  - Three graphics output options: D-Sub, DVI-D and HDMI
  - Soporta HDMI Technology with max. resolution up to 1920x1200 @ 60Hz
  - Soporta DVI-D max. 1920x1200 @ 60Hz
  - Soporta D-Sub max. 1920x1200 @ 60Hz
  - Soporta Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI Port (Compliant HDMI monitor is required)
  - Soporta HDCP with DVI-D and HDMI Ports
  - Soporta Full HD 1080p Blu-ray (BD) playback with DVI-D and HDMI Ports
- Puertos E/S, Conectores:
  - E/S panel trasero:
    - 1 x PS/2 Keyboard
    - 1 x D-Sub
    - 1 x DVI-D
    - 1 x HDMI
  - 3 x USB 2.0 (Soporta ESD Protection (ASRock Full Spike Protection))
  - 1 x USB 3.0 (Soporta ESD Protection (ASRock Full Spike Protection))
  - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED)

- HD Audio Jacks: Line in / Front Speaker / Microphone E/S Internos:
- 1 x Print Port
- 1 x COM Port
- 1 x TPM
- 1 x Chassis Intrusion
- 1 x CPU Fan (3-pin)
- 1 x Chassis Fan (3-pin)
- 1 x 24 pin ATX Power
- 1 x Front Panel Audio
- 2 x USB 2.0 (Support 3 USB 2.0 ports) (Soporta ESD Protection (ASRock Full Spike Protection))
- Otras Características:
  - Audio
  - 5.1 CH HD Audio (Realtek ALC662 Audio Codec)
  - Soporta Surge Protection (ASRock Full Spike Protection) LAN
  - PCIE x1 Gigabit LAN 10/100/1000 Mb/s
  - Realtek RTL8111GR
  - Soporta Wake-On-WAN
  - Soporta Wake-On-LAN
  - Soporta Lightning/ESD Protection (ASRock Full Spike Protection)
  - Soporta LAN Cable Detection
  - Soporta Energy Efficient Ethernet 802.3az
  - Soporta PXE SATA
  - 2 x SATA2 3.0 Gb/s Connectors, support NCQ, AHCI and Hot Plug Certificationes
  - FCC, CE, WHQL
  - ErP/EuP ready (ErP/EuP ready power supply is required)
- Fecha Revisión: 18-06-2014 por FE4

#### Comentarios

Aún no hay comentarios para este producto.