

Punto de Acceso D-Link DWL-2600AP 10 / 100 Mbps PoE 300 Mbps Wifi



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Punto de Acceso D-Link DWL-2600AP 10 / 100 Mbps PoE 300 Mbps Wifi...

Calificación: Sin calificación

Precio

Precio con descuento 81,76 €

Precio de venta 98,92 €

Precio de venta sin impuestos 81,76 €

24 h



[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Punto de Acceso D-Link DWL-2600AP 10 / 100 Mbps PoE 300 Mbps Wifi** al mejor precio.

<p>Marca</p> <p>Modelo</p> <p>Características</p> <p>Otras características</p>	<p>D-Link</p> <p>DWL-2600AP</p> <p>WiFi</p> <ul style="list-style-type: none"> - 802.11a/g/n 2.4 GHz <p>Lan</p> <ul style="list-style-type: none"> - 10/100 Fast Ethernet <p>Ports</p> <ul style="list-style-type: none"> - RJ-45 <p>Antena</p> <ul style="list-style-type: none"> - 2x2 MIMO antena integrada <p>Método alimentación</p> <ul style="list-style-type: none"> - IEEE 802.3af Power Over Ethernet or external power adapter <p>Frecuencia</p> <ul style="list-style-type: none"> - 802.11a/g/n: 2.4 GHz - 2.4835 GHz <p>Tasa de transferencia</p> <ul style="list-style-type: none"> - 802.11a: 6.5 Mbps - 300 Mbps - 802.11g: 54, 48, 36, 24, 18, 12, 9, and 6 Mbps - 802.11n: 11, 5.5, 2 and 1 Mbps <p>Gestión</p> <ul style="list-style-type: none"> - HTTP/HTTPS Web-based User Interface - SNMP, SSH, Telnet Command Line <p>SSID</p> <ul style="list-style-type: none"> - 16 SSID <p>Seguridad inalámbrica</p> <ul style="list-style-type: none"> - Station Isolation - WPA Personal/Enterprise - WPA2 Personal/Enterprise <p>Detección y prevención</p> <ul style="list-style-type: none"> - Rogue and Valid AP Classification <p>Autenticación</p> <ul style="list-style-type: none"> - MAC Address Filtering - 802.1x <p>Alimentación</p> <ul style="list-style-type: none"> - Input: 100 to 240 VAC - Power over Ethernet - 10/100 Mbps PoE (802.3af) input - Stand-Alone Mode - WPA/WPA2 Security - Rogue AP Detection - Station Isolation - MAC Address Filtering - AP Load Balancing Setup - WDS
--	--

- AP Clustering
 - QoS/WMM
 - Local Storage Configuration
Managed Mode
 (Managed by D-Link Wireless Switch/Wireless Controller)
 - Centralized Management
 - Centralized Firmware Dispatch
 - Visualized AP Management Tool
 - Auto-Power Adjustment
 - Dynamic Auto-Channel Selection
 - L2 Fast Roaming
 - L3 Fast Roaming
 - Captive Portal
 - WPA/WPA2 Security
 - Rogue AP Detection
 - Rogue AP Mitigation
 - WIDS
 - Station Isolation
 - MAC Address Filtering
 - AP Load Balancing Setup
 - WDS
 - QoS/WMM
Dimensiones
 - 160 x 160 x 45 mm (6.30" x 6.30" x 1.77")
Peso
 - 240g (0.53 lbs)
EMISIÓN
 - FCC Class B
 - CE Class B
 - IC-SAR
 - IC
 - VCCI
 - NCC
 - TELEC
 - Wi-FiB
Safety
 - cUL
 - LVD (EN60950-1)
 - EN60950-1 2

Fecha de revisión

24-04-2014 por FE4

- Marca: D-Link
- Modelo: DWL-2600AP
- Características:
 - Wi-Fi
 - 802.11b/g/n 2.4 GHz
 - 10/100 Fast Ethernet Puerto
 - RJ-45 Antena
 - 2x2 MIMO antena integrada Método alimentación
 - IEEE 802.3af Power Over Ethernet or external power adapter Frecuencia
 - 802.11b/g/n: 2.4 GHz
 - 2.4835 GHz Tasa de transferencia
 - 802.11n: 6.5 Mbps
 - 300 Mbps
 - 802.11g: 54, 48, 36, 24, 18, 12, 9, and 6 Mbps
 - 802.11b: 11, 5.5, 2 and 1 Mbps Gestión
 - HTTP/HTTPS Web-based User Interface
 - SNMP, SSH, Telnet Command Line SSID
 - 16 SSID
 - Station Isolation Seguridad wireless
 - WPA Personal/ Enterprise
 - WPA2 Personal/ Enterprise Detección y prevención
 - Rogue and Valid AP Classification Autenticación
 - MAC Address Filtering
 - 802.1x.
- Otras características:
 - Alimentación
 - Input: 100 to 240 VAC Power over Ethernet
 - 10/100 Mbps PoE (802.3af) input Stand-Alone Mode
 - WPA/WPA2 Security
 - Rogue AP Detection
 - Station Isolation
 - MAC Address Filtering
 - AP Load Balancing Setup
 - WDS
 - AP Clustering
 - QoS/WMM
 - Local Storage Configuration Managed Mode (Managed by D-Link Wireless Switch/Wireless Controller)
 - Centralized Management
 - Centralized Firmware Dispatch
 - Visualized AP Management Tool
 - Auto-Power Adjustment
 - Dynamic Auto-Channel Selection
 - L2 Fast Roaming
 - L3 Fast Roaming
 - Captive Portal
 - WPA/WPA2 Security
 - Rogue AP Detection
 - Rogue AP Mitigation
 - WIDS
 - Station Isolation
 - MAC Address Filtering
 - AP Load Balancing Setup

- WDS
- QoS/WMM Dimensiones
- 160 x 160 x 45 mm (6.30" x 6.30" x 1.77") Peso
- 240g (0.53 lbs) EMI/EMC/RF
- FCC Class B
- CE Class B
- C-tick,
- IC
- VCCI
- NCC
- TELEC
- Wi-Fi@Safety
- cUL
- LVD (EN60950-1)
- EN60601-1-2
- Fecha de revisión: 24-04-2014 por FE4

Comentarios

Aún no hay comentarios para este producto.