Switch de Sobremesa D-Link EasySmart DGS-1100-16 8 Puertos RJ45 32 Gbit/s 1 Gbit/s Negro

Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Switch de Sobremesa D-Link EasySmart DGS-1100-16 8 Puertos RJ45 32...

Calificación: Sin calificación
Precio
Precio con descuento133,15 €

Precio de venta161,11 €

Precio de venta sin impuestos133,15 €

24 h
★★★★★

Haga una pregunta sobre este producto

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Switch de Sobremesa D-Link EasySmart DGS-1100-16 8 Puertos RJ45 32 Gbit/s 1 Gbit/s Negro** al mejor precio.

Marca	D-Link
Modelo	**DGS-DGS-1100-16**
Especificaciones	**- 16 puertos 10/100/1000 Mbps**

Standards
- IEEE 802.3 compliant
- IEEE 802.3u compliant
- IEEE 802.3ab compliance
- Soporta Half/Full-duplex operation at 10/100Mbps
- Soporta Full-duplex operation at 1000Mbps
- Soporta Auto-Negotiation for each port
- Auto MDI/MDIX
- IEEE 802.3x Flow Control support
- IEEE 802.3az compliant

Rendimiento:
32Gbps
- Max.velocidad envío
23.81 Mpps

- Tamaño tabla MAC
  8K Entries
- Packet Buffer
  3.5Mbits
- Modo envío:
  Store and Forward
- **Alimentación**:
  100 to 240 VAC, 50 to 60 Hz
- Max.Consumo
  11.29 Watts (DGS-1100-08)
- Consumo Standy
  5.64 Watts (DGS-1100-08)
- Sin ventilador
- Nivel acústico:
  0 dBA
- Dimensions (W x D x H)
  280mm x 180mm x 44 mm
- Peso:
  1.5kg
- LEDs
  Power (Per Device)
  PoE Max. (DGS-1100-08P Only)
  Link/Activity/Speed (Per Port)
- Certifications
  FCC Class A
  CE Class A
  VCCI Class A
- Vertificaciones
  UL/cUL
  CE LVD
- MTBF
  988,205 Hours (DGS-1100-08)
- **VLAN**
  Port-based VLAN
  802.1Q Tagged VLAN
  Surveillance VLAN
  Voice VLAN
  Management VLAN
  VLAN Group
    Soporta 32 static VLAN groups
    Max. 4094 VIDs
- **Funciones L2**
  Flow Control
    802.3x Flow Control
    HOL Blocking Prevention
  IGMP Snooping
    IGMP v1/v2 Snooping
    Soporta 32 Groups
  Loopback Detection
  Link Aggregation
    8 groups, 2-4 ports per group (DGS-1100-16/24)
  Port Mirroring
    One-to-One
    Many-to-One (DGS-1100-16/24 only)
  Cable Diagnostics
  Statistics
    Tx Ok
    Tx Error
    Rx Ok
  - Rx Error
- **QoS**
  802.1p Quality of Service
  4 queues per port
  Queue Handling
   Strict
   Weighted Round Robin (WRR)
- **Bandwidth Control**
  DGS-1100-16/24: Port Based (Ingress/Egress, min. granularity 64 kb/s)
- **Seguridad**

Static MAC Address
Max. 128 entries
Broadcast/Multicast/Unknown Unicast Storm Control

- **Gestíon**

Web-Based GUI (Soporta IPv4)
Smart Console Utility

- **D-Link Green**

Power Saving by
Link Status
Cable Length
Energy Efficient Ethernet (IEEE 802.3az)
RoHS Compliant

- **RFC Standard List**

RFC 768 UDP
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 951 BootP Client
RFC 1542 BootP/DHCP client
RFC 1945 HTTP/1.0
RFC 2647 802.1p

Fecha de revisión 03-04-2014 por FE4

Comentarios

Aún no hay comentarios para este producto.